

# TOKU<sup>TM</sup>

## SLUDGE PUMP



TOKU TSLP-150 6" Sludge Pump specially designed to handle clean or dirty water containing limited solids, and mostly use extensively on construction sites for dewatering.

TSLP-150 is automatic priming and re-priming, is by flood lubricating rotary sliding vane vacuum pump.

- High capacity water pump, used for WellPoint dewatering and sump pumping.
- Hard wearing cast iron parts.
- Automatic priming.
- High airflows vacuum system specially designed for dewatering works.
- Hours of unattended operation or intermittent flow.
- Large fuel tank capacity of 140 liters for continuous operation.
- Lifting Hook.
- Key start Engine.
- Available option four wheel site trailer.
- Choice of Engines.

**LISTER HR3**  
**DEUTZ F3L912**



MODEL	TSLP-150	
Type	Self-priming Centrifugal	
Suction x Delivery Diameter (inch)	6" x 6"	
Total Head (m)	33	
Max. Flow (liter/second)	87	
Axle Seal Material	Mechanical Seal (Ceramic-carbon)	
Suction m(ft)	8 (26)	
Engine	LISTER HR3	DEUTZ F3L912
Engine Type :	Air-cooled Gasoline	Air-cooled Diesel
Max. Output (hp/rpm)	22HP / 1500RPM	32HP / 1500RPM
Starting System	Recoil Start	Electric Start
Total Weight (kg)	955	960
Dimension (L x W x H) (mm)	2000 x 1200 x 1650	

*Designs and specifications are subject to change for improvement without prior notice.*

2007 - Rev. 2

LIGHT CONSTRUCTION MACHINERY - 82 TOKU - TSLP-150 SLUDGE PUMP